

**Series 4, wall-mounted cooker hood,  
90 cm, Stainless steel  
DWB96IM50**



**Box-design hood: performance and  
matching kitchen design bundled in one  
hood.**

- **Especially silent:** maximal extractor performance with minimal noise
- **TouchSelect control:** quick touch-control selection of desired settings and light.
- **LED-illumination:** The energy-saving lighting provides white and good lighting for the hob area.
- **Intensive speed setting:** removes strong kitchen odours especially quickly and effectively.
- With exhaust, the air is cleaned by a grease filter and then ducted to the outside which ensures optimal kitchen air quality.

**Technical data**

Typology : Wall-mounted  
 Approval certificates : CE, Eurasian, Morocco, Ukraine, VDE  
 Length electrical supply cord : 130 cm  
 Height of the chimney : 583-912/583-1022 mm  
 Height of product, without chimney : 53 mm  
 Net weight : 13.0 kg  
 Type of control : Electronic  
 : 372 m<sup>3</sup>/h  
 Boost position output recirculating : 441 m<sup>3</sup>/h  
 : 337 m<sup>3</sup>/h  
 Boost position air extraction : 604 m<sup>3</sup>/h  
 Number of lights : 2  
 : 60 dB(A) re 1 pW  
 Diameter of air outlet : 120 / 150 mm  
 Grease filter material : Washable aluminium  
 Odour filter : No  
 Optional accessories : DHZ1225, DHZ1235, DHZ9550,  
 DHZ9551, DWZ1DX1I4, DWZ1DX1I6, DWZ1FX5C6, DWZ1FX5D1,  
 DWZ0DX0A0, DWZ0DX0U0, DWZ0XX0J0, DWZ1DX1B4,  
 DZZ0XX0P0, DZZ1XX1B6  
 Type of lamps used : LED  
 Grease filter type : Kasette  
 : 220 W  
 Fuse protection : 10 A  
 Voltage : 220-240 V  
 Frequency : 50; 60 Hz  
 Plug type : Gardy plug w/ earthing  
 Installation typology : Wall-mounted  
 Material body : Stainless steel  
 Approval certificates : CE, Eurasian, Morocco, Ukraine, VDE  
 Plug type : Gardy plug w/ earthing  
 Dimensions of the product, with chimney (if exists) (in) : / x x  
 Dimensions of the packed product : 19.29 x 25.59 x 40.55  
 Net weight : 29.000 lbs  
 Gross weight : 40.000 lbs  
 Motor location : Integrated motor in hood chimney  
 No-return airflow flap : Yes  
 Length electrical supply cord : 130 cm  
 Dimensions of the product, with chimney (if exists) : 635-1075  
 MM x 900.0 x 500.0 mm  
 Dimensions of the packed product (HxWxD) : 490 x 650 x 1030  
 mm  
 Net weight : 13.0 kg  
 Gross weight : 18.4 kg



## Series 4, wall-mounted cooker hood, 90 cm, Stainless steel DWB96IM50

### Box-design hood: performance and matching kitchen design bundled in one hood.

#### Design:

- Wall mounted hood
- 90 cm Chimney hood
- Box design
- Appliance colour: brushed steel

#### Environment and safety:

- Energy Efficiency Class: B\*
- Average Energy Consumption: 48.5 kWh/year\*
- Blower Efficiency Class: A\*
- Lighting Efficiency Class: A\*
- Grease Filtering Efficiency Class: C\*

#### Comfort:

- TouchControl for extractor speeds and light
- Electronic controls
- T34-BO3AW (white LED)
- TouchControl with Electronic display
- 3 speeds plus intensive setting via TouchControl
- Electronic controls via TouchControl with Electronic display
- TouchControl (3 speeds plus intensive setting) with Electronic display

#### Operating and power:

- Noise min./max. Normal Level: 48/60 dB\*
- 3 speeds plus intensive setting
- Automatic revert setting, 6 minutes
- Max. extraction rate: 604 m<sup>3</sup>/h

#### Power:

- Power rating: 220 W
- Twin channel high performance fan motor
- Capacitor energy efficient

#### Measures:

- 90 cm wide
- Electrical cable length 1.3 m
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Dimensions recirculating (HxWxD): 635-1075 MM x 900 x 500 mm
- Dimensions recirculating with CleanAir module (HxWxD):  
703 x 900 x 500mm - mounting with outer chimney  
833-1163 x 900 x 500 mm - mounting with telescopic chimney

#### Technical information:

- Suitable for ducted or re-circulated extraction
- For recirculated extraction recirculating kit or CleanAir recirculating kit (accessory) needed
- 2 x 1,5W LED
- Light Intensity: 214 lux
- Colour Temperature: 3500 K
- Metal grease filter, dishwasher safe
- with one-way flap
- Maximum extraction rate exhaust air 372 m<sup>3</sup>/h according to EN 61591
- Extraction rate according to EN 61591 Ø 15 cm:  
max. Normal use 372 m<sup>3</sup>/h  
Intensive 604 m<sup>3</sup>/h
- Extraction rate exhaust air according to EN 61591:  
max. normal use 372 m<sup>3</sup>/h, intensive 604 m<sup>3</sup>/h
- Noise level according to EN 60704-3 und EN 60704-2-13 exhaust air:  
Max. normal use: 60 dB(A) re 1 pW (47 dB(A) re 20 µPa sound pressure)  
Intensive: 70 dB(A) re 1 pW (57 dB(A) re 20 µPa sound pressure)

\* In accordance with the EU-Regulation No 65/2014

**Series 4, wall-mounted cooker hood, 90 cm,  
Stainless steel  
DWB96IM50**

