

**Serie | 4, , 60 cm, clear glass black printed  
DWK67HM60**



**Inclined hood: optimal for keeping an eye on your pots and pans.**

- **Especially silent:** maximal extractor performance with minimal noise
- **Easy-to-clean interior:** hidden screws and cables along with rounded edges make cleaning easy.
- **TouchSelect control:** quick touch-control selection of desired settings and light.
- **LED-Illumination:** The energy-saving lighting provides white and good lighting for the hob area.
- **Intensive speed setting:** removes strong kitchen odours especially quickly and effectively.

**Technical data**

Typology :	Chimney
Approval certificates :	CE, Eurasian, Ukraine, VDE
Length electrical supply cord (cm) :	130
Height of product, without chimney (mm) :	323
Net weight (kg) :	19.646
Type of control :	Electronic
:	416
Boost position output recirculating (m <sup>3</sup> /h) :	615.0
:	409
Boost position air extraction (m <sup>3</sup> /h) :	700
Number of lights :	2
:	58
Diameter of air outlet (mm) :	120 / 150
Grease filter material :	Washable aluminium
Odour filter :	No
Optional accessories :	
DWZ0AK0R0, DWZ0AK0S0, DWZ0AX5K0, DWZ0AX5L0, DWZ1AK1B6, DWZ1AK1I6, DWZ1AK1V6, DWZ1AX5C6, DWZ1AX6E1, DZZ0XX0P0, DZZ1XX1B6, HEZG9AS00S	
Type of lamps used :	LED
Grease filter type :	Kassette
:	263
Current (A) :	10
Voltage (V) :	220-240
Frequency (Hz) :	50; 60
Plug type :	Gardy plug w/ earthing
Installation typology :	Wall-mounted
Material body :	Glass, Lacquered
Approval certificates :	CE, Eurasian, Ukraine, VDE
Plug type :	Gardy plug w/ earthing
Dimensions of the product, with chimney (if exists) (in) :	/ x x
Dimensions of the packed product (in) :	27.16 x 29.13 x 40.94
Net weight (lbs) :	43.000
Gross weight (lbs) :	63.000
Motor location :	Integrated motor in hood body
No-return airflow flap :	Yes
Length electrical supply cord (cm) :	130
Dimensions of the product, with chimney (if exists) (mm) :	453 x 590.0 x 499.0
Dimensions of the packed product (HxWxD) (mm) :	690 x 740 x 1040
Net weight (kg) :	19.646
Gross weight (kg) :	28.5



## Serie | 4, , 60 cm, clear glass black printed DWK67HM60

### Inclined hood: optimal for keeping an eye on your pots and pans.

#### Design:

- Chimney hood
- Inclined design
- black with glass canopy
- Appliance colour: black
- Wall mounted hood
- Filter cover glass
- Glass plate: clear glass black printed
- 2 capture areas: front side and bottom side

#### Environment and safety:

- Energy Efficiency Class: B\*
- Average Energy Consumption: 56.6 kWh/year\*
- Blower Efficiency Class: B\*
- Lighting Efficiency Class: B\*
- Grease Filtering Efficiency Class: C\*

#### Comfort:

- Wall fixing inclined/flat/cube
- TouchControl for extractor speeds and light
- 3 speeds plus intensive setting via TouchControl
- Electronic controls via TouchControl with Electronic display
- TouchControl (3 speeds plus intensive setting) with Electronic display
- easy to clean Innerframe
- RimVentilation
- Metal grease filter, dishwasher safe

#### Operating and power:

- 3 speeds plus intensive setting
- Automatic revert setting, 6 minutes
- Max. extraction rate: 700 m<sup>3</sup>/h

#### Power:

- Power rating: 263 W
- Twin channel high performance fan motor
- Capacitor energy efficient
- Light Intensity: 100 lux

#### Measures:

- 60 cm
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Dimensions recirculating, chimney (HxWxD): 989-1259 x 590 x 499 mm
- Dimensions recirculating with CleanAir module (HxWxD): 1119 x 590 x 499 mm - mounting with outer chimney  
1189-1459 x 590 x 499 mm - mounting with telescopic chimney
- Dimensions recirculating, chimless (HxWxD): 453 mm x 590 x 499 mm

#### Technical information:

- 2 x 1,5W LED
- Noise min./max. Normal Level: 48/58 dB\*
- Suitable for ducted or re-circulated extraction
- In recirculation operation chimless use possible
- For recirculated extraction a recirculating kit or a CleanAir recirculation kit (accessory) is needed
- Extraction rate according to EN 61591 ø 15 cm:  
max. Normal use 416 m<sup>3</sup>/h  
Intensive 700 m<sup>3</sup>/h
- Extraction rate exhaust air according to EN 61591:  
max. normal use 416 m<sup>3</sup>/h, intensive 700 m<sup>3</sup>/h
- Extraction rate in recirculation mode:  
Max. normal use: 409 m<sup>3</sup>/h  
Intensive: 615 m<sup>3</sup>/h
- Noise level according to EN 60704-3 und EN 60704-2-13 at max. normal use exhaust air: 58 dB(A) re 1 pW (45 dB(A) re 20 µPa sound pressure)
- Noise level according to EN 60704-3 und EN 60704-2-13 exhaust air:  
Max. normal use: 58 dB(A) re 1 pW (45 dB(A) re 20 µPa sound pressure)  
Intensive: 67 dB(A) re 1 pW (54 dB(A) re 20 µPa sound pressure)
- Colour Temperature: 3500 K

\* In accordance with the EU-Regulation No 65/2014

**Serie | 4, , 60 cm, clear glass black printed  
DWK67HM60**

