

## Series 4, Island Extractor Hood, 90 cm, Stainless steel DIB97IM50



B



DHZ1256 Chimney extension 1600 mm, DHZ5346 Standard odor filter (replacement), DHZ5385 Standard recirculation kit, DIZ2CB114 Clean Air Standard recirculation kit, DIZ2CX5C6 Clean Air Plus recirc. kit external, DIZ2FX5D1 Long Life recirculation kit external, DZZ0XX0P0 Long Life odor filter (replacement), DZZ1XX1B6 Clean Air Plus odor filter (replacement), DHZ1231 Adapter for roof inclination left/right, DHZ1241 Adapter for roof inclination front/back, DHZ1246 Chimney extension 1100 mm, DHZ1251 Extension for mounting kit 500 mm, DHZ1253 Extension for mounting kit 1000 mm, DZZ2CB1B4 Clean Air Standard odor filter (repl.), HEZG9AS00S Adapter

## The island chimney hood: the perfect solution for your cooking island thanks to flexible ceiling mounting.

- **Especially silent:** maximal extractor performance with minimal noise
- **Easy-to-clean interior:** hidden screws and cables along with rounded edges make cleaning easy.
- **TouchSelect control:** quick touch-control selection of desired settings and light. TouchSelect control: quick touch-control selection of desired settings and light.

Typology: .....Island/Ceiling  
 Length electrical supply cord: ..... 130.0 cm  
 Height of the chimney: ..... 691-871/691-991 mm  
 Height of the appliance: ..... 53 mm  
 Minimum distance above an electric hob: ..... 550 mm  
 Minimum distance above a gas hob: ..... 650 mm  
 Net weight: ..... 29.2 kg  
 Type of control: .....Electronic  
 Number of speed settings: ..... 3-stages + intensive setting  
 Max. air extraction: .....438 m<sup>3</sup>/h  
 Boost position output recirculating: ..... 527 m<sup>3</sup>/h  
 Max. air recirculation: ..... 390 m<sup>3</sup>/h  
 Boost position air extraction: ..... 754 m<sup>3</sup>/h  
 Maximum Air flow: .....438 m<sup>3</sup>/h  
 Number of lights: ..... 4  
 Noise level: .....57 dB(A) re 1 pW  
 Diameter of air outlet: ..... 150 / 120 mm  
 Grease filter material: .....Washable aluminium  
 EAN code: ..... 4242005086269  
 Connection rating: ..... 256 W  
 Fuse protection: .....10 A  
 Voltage: ..... 220-240 V  
 Frequency: ..... 60; 50 Hz  
 Plug type: ..... Gardy plug w/ earthing  
 Installation typology: ..... Island



## Series 4, Island Extractor Hood, 90 cm, Stainless steel DIB97IM50

### The island chimney hood: the perfect solution for your cooking island thanks to flexible ceiling mounting.

- Dimensions recirculating (HxWxD): 744-1044 x 898 x 600 mm
- Power rating: 256 W
- Electrical cable length 1.3 m
- Voltage: 220 - 240 V

- Energy Efficiency Class: B\*
- Average Energy Consumption: 74.3 kWh/year\*
- Blower Efficiency Class: B\*
- Lighting Efficiency Class: A\*
- Grease Filtering Efficiency Class: B\*
- Noise max. Normal Level: 57 dB\*

#### Technical information:

- Island extractor
- 90 cm wide
- Brushed steel
- Suitable for ducted or recirculating operation
- Recirc. kit or clean air kit
- Designed for ceiling mounted installation
- touch control for extractor speeds and light
- Electronic controls
- touch control with Electronic display
- 3 speed + intensive operation via touch control
- Electronic controls via touch control with Electronic display
- touch control (3 speed + intensive operation) with Electronic display
- 3 speed + intensive operation
- Intensive op. revert dur.: 6 min.
- Easy to clean
- 4 x 1,5W LED
- Light Intensity: 409 lux
- Colour Temperature: 3500 K
- Removable metal grease filters, dishwasher safe
- Extraction rate according to DIN/EN 61591  $\varnothing$  15 cm: max. Normal 438 m<sup>3</sup>/h Intensive 754 m<sup>3</sup>/h
- Ducted extraction rate according to DIN/EN 61591 max. 438 m<sup>3</sup>/h
- Maximum extraction 438 m<sup>3</sup>/h
- Extraction rate exhaust air according to EN 61591:
  - max. normal use 438 m<sup>3</sup>/h, intensive 754 m<sup>3</sup>/h
- Dimensions recirculating with CleanAir module (HxWxD): 812-1044 x 898 x 600 mm
- Additional noise insulation
- Noise level according to EN 60704-3 und EN 60704-2-13 at max. normal use exhaust air: 57 dB(A) re 1 pW (44 dB(A) re 20  $\mu$ Pa sound pressure)
- Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air:
  - Max. normal use: 57 dB(A) re 1 pW (44 dB(A) re 20  $\mu$ Pa sound pressure)
  - Intensive: 68 dB(A) re 1 pW (55 dB(A) re 20  $\mu$ Pa sound pressure)
- Diameter pipe  $\varnothing$  150 mm ( $\varnothing$  120 mm enclosed)
- Yes
- Max. extraction rate: 754 m<sup>3</sup>/h
- Dimensions exhaust air (HxWxD): 744-924 x 898 x 600 mm

**Series 4, Island Extractor Hood, 90 cm, Stainless steel  
DIB97IM50**

