

**Series 4, Wall-mounted Extractor Hood, 60 cm, clear glass DWG66CD50Z**



**B**

**The wall-mounted chimney hood: mount it on the wall, giving you complete freedom in your kitchen planning.**

- **silent:** maximal extractor performance with little noise
- **Intensive speed setting:** removes strong kitchen odours especially quickly and effectively.
- **Metal Grease Filter:** cleans the air, captures grease, easy monthly clean-up.

---

Typology: .....Wall-mounted  
 Length electrical supply cord: ..... 100.0 cm  
 Height of the chimney: ..... 730-890/730-1000 mm  
 Minimum distance above an electric hob: ..... 500 mm  
 Minimum distance above a gas hob: .....650 mm  
 Net weight: .....19.2 kg  
 Type of control: .....Electronic  
 Number of speed settings: ..... 3-stages + intensive setting  
 Max. air extraction: ..... 620 m<sup>3</sup>/h  
 Boost position output recirculating: ..... 440.0 m<sup>3</sup>/h  
 Max. air recirculation: ..... 415 m<sup>3</sup>/h  
 Boost position air extraction: ..... 700 m<sup>3</sup>/h  
 Maximum Air flow: .....620 m<sup>3</sup>/h  
 Number of lights: ..... 2  
 Noise level: .....63 dB(A) re 1 pW  
 Diameter of air outlet: ..... 150 mm  
 Grease filter material: .....Washable aluminium  
 EAN code: ..... 4242002985398  
 Connection rating: ..... 252 W  
 Voltage: ..... 220-240 V  
 Frequency: ..... 50-60 Hz  
 Plug type: .....No plug (electrical connection by electrician)  
 Installation typology: .....Wall-mounted

---



## **Series 4, Wall-mounted Extractor Hood, 60 cm, clear glass DWG66CD50Z**

**The wall-mounted chimney hood: mount it  
on the wall, giving you complete freedom  
in your kitchen planning.**

---

- Brushed steel with glass canopy

**Technical information:**

- Suitable for ducted or recirculating operation
- 3 speed + intensive operation
- Removable metal grease filters, dishwasher safe
- Extraction rate exhaust air according to EN 61591:
  - max. normal use 620 m<sup>3</sup>/h, intensive 700 m<sup>3</sup>/h
- Energy Efficiency Class: B\*
- Diameter pipe Ø 150 mm (Ø 150 mm enclosed)
- Power rating: 252 W
- Dimensions exhaust air (HxWxD): 778-938 x 598 x 520 mm
- Dimensions recirculating (HxWxD): 778-1048 x 598 x 520 mm

**Series 4, Wall-mounted Extractor**  
**Hood, 60 cm, clear glass**  
**DWG66CD50Z**

