

**Series 2, Wall-mounted Extractor Hood, 60 cm, Stainless steel
DWP64CC50Z**



The wall-mounted chimney hood: mount it on the wall, giving you complete freedom in your kitchen planning.

- **silent:** maximal extractor performance with little noise
- **Metal grease filters:** filter grease and other solid particles out of the extracted air

DWA0KP6A Standard odor filter
DWZ6HP1U2 Standard recirculation kit

Typology:Wall-mounted
 Length electrical supply cord: 120.0 cm
 Height of the chimney: 410-765/410-765 mm
 Height of the appliance: 250 mm
 Minimum distance above an electric hob: 650 mm
 Minimum distance above a gas hob: 650 mm
 Net weight: 11.0 kg
 Type of control: mechanical
 Number of speed settings: 3
 Max. air extraction: 380 m³/h
 Max. air recirculation: 235 m³/h
 Maximum Air flow: 380 m³/h
 Number of lights: 2
 Noise level: 64 dB(A) re 1 pW
 Diameter of air outlet: 150 mm
 Grease filter material:Washable aluminium
 EAN code: 4242002985336
 Connection rating: 135 W
 Voltage: 220-240 V
 Frequency: 50 Hz
 Plug type:No plug (electrical connection by electrician)
 Installation typology:Wall-mounted



Series 2, Wall-mounted Extractor
Hood, 60 cm, Stainless steel
DWP64CC50Z

