

**Series 2, Wall-mounted Extractor Hood, 90 cm, Stainless steel  
DWP94CC50M**



DWA0KP6A Standard odor filter  
DWZ6HP1U2 Standard recirculation kit

**The wall-mounted chimney hood: mount it on the wall, giving you complete freedom in your kitchen planning.**

- **silent:** maximal extractor performance with little noise
- **Metal grease filters:** filter grease and other solid particles out of the extracted air

Typology: .....Wall-mounted  
 Length electrical supply cord: ..... 120.0 cm  
 Height of the chimney: ..... 410-765/410-765 mm  
 Height of the appliance: ..... 250 mm  
 Minimum distance above an electric hob: ..... 650 mm  
 Minimum distance above a gas hob: ..... 650 mm  
 Net weight: ..... 13.7 kg  
 Type of control: ..... mechanical  
 Number of speed settings: ..... 3  
 Max. air extraction: ..... 380 m<sup>3</sup>/h  
 Max. air recirculation: ..... 235 m<sup>3</sup>/h  
 Maximum Air flow: ..... 380 m<sup>3</sup>/h  
 Number of lights: ..... 2  
 Noise level: ..... 64 dB(A) re 1 pW  
 Diameter of air outlet: ..... 150 mm  
 Grease filter material: .....Washable aluminium  
 EAN code: ..... 4242005033300  
 Connection rating: ..... 135 W  
 Voltage: ..... 220-240 V  
 Frequency: ..... 50 Hz  
 Plug type: ..... GB plug  
 Installation typology: .....Wall-mounted



## Series 2, Wall-mounted Extractor Hood, 90 cm, Stainless steel DWP94CC50M

**The wall-mounted chimney hood: mount it on the wall, giving you complete freedom in your kitchen planning.**

- DWP94CC50M
- 90 cm, Chimney extractor hood

### **Design:**

- Brushed steel
- Designed for wall mounted installation

### **Comfort and Safety:**

- Energy Efficiency Class: D\*
- Blower Efficiency Class: E\*
- Lighting Efficiency Class: A\*
- Grease Filtering Efficiency Class: C\*
- Average Energy Consumption: 72.8 kWh/year\*

### **Comfort:**

- push buttons for extractor speeds and light
- Removable metal grease filters, dishwasher safe

### **Operating and power:**

- Suitable for ducted or re-circulated extraction
- 3 speed operation
- Power rating: 135 W

### **Measures:**

- 150 mm diameter pipe
- Ducted extraction rate according to DIN/EN 61591 max. 380 m<sup>3</sup>/h
- Dimensions exhaust air (HxWxD): 790-1015 x 898 x 470 mm
- Dimensions recirculating (HxWxD): 790-1015 x 898 x 470 mm
- Noise level according to EN 60704-3 und EN 60704-2-13 at max. normal use exhaust air: 64 dB(A) re 1 pW (50 dB(A) re 20 µPa sound pressure)
- Noise max. Normal Level: 64 dB\*
- Light Intensity: 1000 lux
- Colour Temperature: 4000 K

\* In accordance with the EU-Regulation No 65/2014

**Series 2, Wall-mounted Extractor**  
**Hood, 90 cm, Stainless steel**  
**DWP94CC50M**

