

Serie | 2
DWW09W650Z
90 cm, Chimney extractor hood

The wall-mounted chimney hood: mount it on the wall, giving you complete freedom in your kitchen planning.

- **Extraction rate:** at 650 m³/h, it quickly ensures optimal kitchen air quality.
- **Halogen lighting:** for optimal, energy-efficient illumination of the hob.
- **Especially quiet:** high performance at just 55 dB.

Technical data

Color chimney :	Stainless steel
Typology :	Chimney
Approval certificates :	CE, VDE
Length electrical supply cord (cm) :	130
Height of the chimney (mm) :	553-730/573-730
Height of product, without chimney (mm) :	246
Net weight (kg) :	10.298
Type of control :	mechanical
Number of speed settings :	3
Maximum output air extraction (m ³ /h) :	650
Maximum output recirculating air (m ³ /h) :	370
Number of lights :	2
Noise level (dB(A) re 1 pW) :	69
Diameter of air outlet (mm) :	150 / 120
Grease filter material :	Washable aluminium
Odour filter :	No
Operating Mode :	Convertible
Optional accessories : DHZ1224, DHZ1234, DHZ5275, DHZ5276	
Type of lamps used :	Halogen
Total power of the lamps (W) :	60
Grease filter type :	Kassette
Connection Rating (W) :	235
Current (A) :	10
Voltage (V) :	220-240
Frequency (Hz) :	50; 60
Plug type :	South Africa plug
Installation typology :	Wall-mounted
Material body :	Stainless steel
Approval certificates :	CE, VDE
Plug type :	South Africa plug
Dimensions of the product, with chimney (if exists) (in) :	/ x x
Dimensions of the packed product (in) :	13.38 x 23.42 x 38.77
Net weight (lbs) :	23
Gross weight (lbs) :	31
Motor location :	Integrated motor in hood body
No-return airflow flap :	No
Length electrical supply cord (cm) :	130
Dimensions of the product, with chimney (if exists) (mm) :	799-976 x 900 x 500
Dimensions of the packed product (HxWxD) (mm) :	340 x 595 x 985
Net weight (kg) :	10.298
Gross weight (kg) :	14.0



Serie | 2 Hoods

DWW09W650Z

90 cm, Chimney extractor hood

The wall-mounted chimney hood: mount it on the wall, giving you complete freedom in your kitchen planning.

-
- Designed for wall mounted installation
 - Suitable for ducted or recirculating operation
 - Twin channel high performance fan motor
 - Switch control for extractor speeds and light
 - 3 speed operation
 - Maximum extraction 650 m³/h
 - Noise level according to EN 60704-3 und EN 60704-2-13 at max. normal use exhaust air: 69 dB(A) re 1 pW (55 dB(A) re 20 µPa sound pressure)
 - 2 x high volt halog. light 30W
 - Removable metal grease filters, dishwasher safe
 - Power rating: 235 W
 - Dimensions exhaust air (HxWxD): 799-976 x 900 x 500 mm
 - Dimensions recirculating (HxWxD): 799-976 x 900 x 500 mm
 - Average Energy Consumption: 109.8 kWh/year*

Serie | 2 Hoods

DWW09W650Z

90 cm, Chimney extractor hood

