

iQ700, Wall-mounted Extractor Hood, 120 cm, Stainless steel LC21BD552

A



The wall-mounted chimney hood with high extraction rate – perfect for installing on the kitchen wall.

- ✓ The 810 m³/h extraction rate supplies clean air when cooking.
- ✓ The energy-saving LED lighting ensures optimal visibility when cooking.
- ✓ The intensive setting temporarily increases the extraction rate when kitchen vapour is especially intense, with automatic revert after 6 min.
- ✓ Extremely quiet at a mere 49 dB.

Features

Technical data

Typology : Chimney
 Approval certificates : CE, VDE
 Length electrical supply cord (cm) : 130
 Height of the chimney (mm) : 582-908/582-1018
 Height of product, without chimney (mm) : 46
 Net weight (kg) : 23.600
 Type of control : Electronic
 Number of speed settings : 3-stage + 2 intensive
 Maximum output air extraction (m³/h) : 633
 Boost position output recirculating (m³/h) : 430.0
 Boost position air extraction (m³/h) : 810
 Number of lights : 4
 Noise level (dB(A) re 1 pW) : 62
 Diameter of air outlet (mm) : 150 / 120
 Grease filter material : Washable stainless steel
 Odour filter : No
 Operating Mode : Convertible
 Delay Shut off modes : 10M
 Optional accessories : LZ00XP00, LZ12265, LZ12365, LZ53450, LZ53451, LZ56200, LZ57300
 Type of lamps used : LED
 Total power of the lamps (W) : 12
 Grease filter type : Multilayer
 Connection Rating (W) : 272
 Current (A) : 10
 Voltage (V) : 220-240
 Frequency (Hz) : 50; 60
 Plug type : Gardy plug w/ earthing
 Installation typology : Wall-mounted
 Material body : Stainless steel
 Approval certificates : CE, VDE
 Plug type : Gardy plug w/ earthing
 Dimensions of the product, with chimney (if exists) (in) : / x x
 Dimensions of the packed product (in) : 22.83 x 24.01 x 51.57
 Net weight (lbs) : 52
 Gross weight (lbs) : 76
 Motor location : Integrated motor in hood chimney
 No-return airflow flap : Yes
 Length electrical supply cord (cm) : 130
 Dimensions of the product, with chimney (if exists) (mm) : 628-1064 x 1200.0 x 500.0
 Dimensions of the packed product (HxWxD) (mm) : 580 x 610 x 1310
 Net weight (kg) : 23.600
 Gross weight (kg) : 34.6

Optional accessories

LZ56200	CleanAir active carbon filter spare part
LZ53450	Standard recirculation kit



4 242003 674925

iQ700, Wall-mounted Extractor Hood, 120 cm, Stainless steel LC21BD552

Features

- Energy Efficiency Class: A*
- Average Energy Consumption: 43.2 kWh/year*
- Noise max. Normal Level: 63 dB*
- 120 cm stainless steel Chimney hood with glass canopy
- stainless steel
- Ducted/Recirculating operation
- Recirc. kit or clean air kit
- Designed for wall mounted installation
- Chimney hood wall fixing syst.
- Inner frame: yes
- light conception white/blue
- Push button controls with 7-segment display
- 3-stage + 2 intensive
- Intensive op. revert dur.: 6 min.
- Air quality sensor
- Boost function
- Twin channel high performance fan motor
-
-
- Light dimmer function
- softLight
- Metal grease filter with side extraction
- Filter cover stainless steel
- Removable metal grease filters, dishwasher safe
- grease- and charcoal filter
- Additional noise insulation
- Dimensions exhaust air (HxWxD): 628-954 x 1200 x 500 mm
- Dimensions recirculating (HxWxD): 628-1064 x 1200 x 500 mm
- Dimensions recirculating with cleanAir module (HxWxD);
- 689 x 1200 x 500 mm - mounting with outer chimney
- 809-1139 x 1200 x 500 mm - mounting with telescopic chimney
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Power rating: 272 W

**iQ700, Wall-mounted Extractor Hood,
120 cm, Stainless steel
LC21BD552**

Dimensioned drawings

