

iQ100
LC64PCC50Z
60 cm, Chimney hood



The wall-mounted chimney hood: mount it on the wall, giving you complete freedom in your kitchen planning.

- ✓ Extraction rate: at 380 m³/h, it quickly ensures optimal kitchen air quality.
- ✓ LED lighting: for perfect, very energy-efficient illumination of the hob.
- ✓ Especially quiet: high performance at just 54 dB.

Features

Technical data

Color chimney : Stainless steel
 Typology : Chimney
 Approval certificates : CE, VDE
 Length electrical supply cord (cm) : 120
 Height of the chimney (mm) : 410-765/410-765
 Height of product, without chimney (mm) : 250
 Net weight (kg) : 9.578
 Type of control : mechanical
 Number of speed settings : 3
 Maximum output air extraction (m³/h) : 380
 Maximum output recirculating air (m³/h) : 235
 Number of lights : 2
 Noise level (dB(A) re 1 pW) : 64
 Diameter of air outlet (mm) : 150
 Grease filter material : Washable aluminium
 Odour filter : No
 Operating Mode : Convertible
 Optional accessories : LA10KPA6
 Type of lamps used : LED
 Total power of the lamps (W) : 10
 Grease filter type : Kassette
 Connection Rating (W) : 135
 Voltage (V) : 220-240
 Frequency (Hz) : 50
 Plug type : no plug
 Installation typology : Wall-mounted
 Material body : Stainless steel
 Approval certificates : CE, VDE
 Plug type : no plug
 Dimensions of the product, with chimney (if exists) (in) : / x x
 Dimensions of the packed product (in) : 24.80 x 25.59 x 16.53
 Net weight (lbs) : 21
 Gross weight (lbs) : 25
 Motor location : Integrated motor in hood body
 No-return airflow flap : No
 Length electrical supply cord (cm) : 120
 Dimensions of the product, with chimney (if exists) (mm) : 790-1015 x 598 x 470
 Dimensions of the packed product (HxWxD) (mm) : 630 x 650 x 420
 Net weight (kg) : 9.578
 Gross weight (kg) : 11.0



iQ100

LC64PCC50Z

60 cm, Chimney hood

Features

- stainless steel
- Designed for wall mounted installation
- Suitable for ducted or re-circulated extraction
- 3 speed control
- Push buttons for extractor speeds and light
- Removable metal grease filters, dishwasher safe
- Dimensions exhaust air (HxWxD): 790-1015 x 598 x 470 mm
- Suitable for ducted or re-circulated extraction
- Dimensions recirculating (HxWxD): 790-1015 x 598 x 470 mm
- Power rating: 135 W
- 150 mm diameter pipe
- Energy Efficiency Class: D*
- Noise max. Normal Level: 64 dB*

iQ100
 LC64PCC50Z
 60 cm, Chimney hood

Dimensioned drawings

