

iQ300
LC66GCD50Z
Glass common design
60 cm, Chimney hood
stainless steel with glass canopy

B



The wall-mounted chimney hood: mount it on the wall, giving you complete freedom in your kitchen planning.

- ✓ Extraction rate: at 700 m³/h, it quickly ensures optimal kitchen air quality.
- ✓ LED lighting: for perfect, very energy-efficient illumination of the hob.
- ✓ Especially quiet: high performance at just 54 dB.

Features

Technical data

Color chimney : Stainless steel
 Typology : Chimney
 Approval certificates : CE, VDE
 Length electrical supply cord (cm) : 100
 Height of the chimney (mm) : 730-890/730-1000
 Net weight (kg) : 9.578
 Type of control : Electronic
 Maximum output air extraction (m³/h) : 620
 Boost position output recirculating (m³/h) : 440
 Maximum output recirculating air (m³/h) : 415
 Boost position air extraction (m³/h) : 700
 Number of lights : 2
 Noise level (dB(A) re 1 pW) : 63
 Diameter of air outlet (mm) : 150
 Grease filter material : Washable aluminium
 Odour filter : No
 Operating Mode : Convertible
 Type of lamps used : LED
 Total power of the lamps (W) : 2
 Grease filter type : Kasette
 Connection Rating (W) : 252
 Voltage (V) : 220-240
 Frequency (Hz) : 50-60
 Plug type : no plug
 Installation typology : Wall-mounted
 Material body : Glass, Stainless steel
 Approval certificates : CE, VDE
 Plug type : no plug
 Dimensions of the product, with chimney (if exists) (in) : / x x
 Dimensions of the packed product (in) : 24.80 x 25.59 x 16.53
 Net weight (lbs) : 21
 Gross weight (lbs) : 25
 Motor location : Integrated motor in hood chimney
 No-return airflow flap : No
 Length electrical supply cord (cm) : 100
 Dimensions of the product, with chimney (if exists) (mm) : 778-1048 x 598 x 520
 Dimensions of the packed product (HxWxD) (mm) : 630 x 650 x 420
 Net weight (kg) : 9.578
 Gross weight (kg) : 11.0



iQ300
LC66GCD50Z
Glass common design
60 cm, Chimney hood
stainless steel with glass canopy

Features

Technical information:

-
-
- Ducted/Recirculating operation
- Push button controls,
- 3 speed control plus intensive setting
- Removable metal grease filters, dishwasher safe
- Energy Efficiency Class: B*
- Diameter pipe Ø 150 mm (Ø 150 mm enclosed)
- Power rating: 252 W
- Dimensions exhaust air (HxWxD): 778-938 x 598 x 520 mm
- Dimensions recirculating (HxWxD): 778-1048 x 598 x 520 mm

iQ300
LC66GCD50Z
Glass common design
60 cm, Chimney hood
stainless steel with glass canopy

Dimensioned drawings

