

iQ100, Wall-mounted Extractor Hood, 90 cm, clear glass black printed LC95KA670



LA10LKA6 Standard odor filter

The wall-mounted chimney hood with high extraction rate – perfect for installing on the kitchen wall.

✓ LED light: For optimal visibility and atmosphere when cooking.



Typology: Wall-mounted
 Length electrical supply cord: 130.0 cm
 Height of the appliance: 354 mm
 Minimum distance above an electric hob: 470 mm
 Minimum distance above a gas hob: 570 mm
 Net weight: 11.1 kg
 Type of control: Electronic
 Number of speed settings: 3
 Max. air extraction: 629 m³/h
 Max. recirculation: 230 m³/h
 Maximum Air flow: 629 m³/h
 Number of lights: 2
 Noise level: 67 dB(A) re 1 pW
 Diameter of air outlet: 150 / 120 mm
 Grease filter material: Washable aluminium
 EAN code: 4242003809556
 Connection rating: 216 W
 Fuse protection: 10 A
 Voltage: 220-240 V
 Frequency: 50 Hz
 Plug type: Gardy plug w/ earthing
 Installation typology: Wall-mounted



iQ100, Wall-mounted Extractor Hood, 90 cm, clear glass black printed LC95KA670

Design:

Operating and power:

Power:

Comfort and Safety:

Comfort:

Measures:

Technical information:

- Energy Efficiency Class: C*
- Average Energy Consumption: 94.5 kWh/year*
- Blower Efficiency Class: D*
- Lighting Efficiency Class: A*
- Grease Filtering Efficiency Class: D*
- Noise max. Normal Level: 67 dB*
- 90 cm black Chimney hood with glass canopy
- black with glass canopy
- Glass plate clear glass black printed
- Suitable for ducted extraction and recirculation
- Recirculating kit
- Designed for wall mounted installation
- touch control with Electronic display
- 3 speed control
- Light Intensity: 377 lux
- Colour Temperature: 3000 K
- Metal grease filter with side extraction
- Filter cover glass
- Removable metal grease filters, dishwasher safe
- Maximum extraction 629 m³/h
- Noise level according to EN 60704-3 und EN 60704-2-13 at max. normal use exhaust air: 67 dB(A) re 1 pW (55 dB(A) re 20 µPa sound pressure)
- Dimensions exhaust air (HxWxD): 750-1080 x 896 x 386 mm
- Dimensions recirculating (HxWxD): 862-1080 x 896 x 386 mm
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Power rating: 216 W

* In accordance with the EU-Regulation No 65/2014

iQ100, Wall-mounted Extractor Hood, 90 cm, clear glass black printed LC95KA670

