

**Series 4, Gas Hob, 60 cm, Stainless steel
PGP6B5B62Z**



HEZ298105 Simmer plate
HEZ298115 Small pot support

**The gas hob with front-mounted controls:
the desired cooking zones can be
conveniently operated from the front.**

- **Continuous cast-iron finish pan supports:** for maximum stability.
- **Sword knobs:** for an ergonomic control.
- **Safety solution for your gas hob.**
- **Prompt and effective solution.**
- **Surface colour: elegant stainless-steel design.**

Product name/family:gas hob w integrated controls
 Built-in / Free-standing: Built-in
 Energy input:Gas
 Total number of positions that can be used at the same time: 4
 Type of control setting devices: sword knobs
 Min. required niche size for installation (HxWxD):45 x 560-562 x 480-492 mm
 Width of the appliance: 582 mm
 Dimensions: 53 x 582 x 520 mm
 Dimensions of the packed product (HxWxD): 141 x 651 x 578 mm
 Net weight: 7.9 kg
 Gross weight: 8.8 kg
 Residual heat indicator:No
 Location of control panel: Front
 Basic surface material: Stainless steel
 Color of surface: Stainless steel
 Length electrical supply cord: 150.0 cm
 EAN code: 4242005298808
 Gas connection rating: 7500 W
 Fuse protection:3 A
 Voltage: 220-240 V
 Frequency: 50; 60 Hz



Series 4, Gas Hob, 60 cm, Stainless steel PGP6B5B62Z

**The gas hob with front-mounted controls:
the desired cooking zones can be
conveniently operated from the front.**

Design

- Stainless steel surface
- Cast iron finish w rubber feet

Comfort & Convenience

- Sword Knobs: easily access knobs in front with strong grip for effortless turning.
- Ignition via control knobs: just push and turn the knob to ignite the flame.

Burners and power

- 4 PC
- Left front: Standard burner up to 1.75 KW (depending on gas type)
- Left rear: Standard burner up to 1.75 KW (depending on gas type)
- Right rear: High speed burner up to 3 KW (depending on gas type)
- Right front: Economy burner up to 1 KW (depending on gas type)

Safety

- Flame failure safety device: prevents unwanted gas flow when flame goes out.

Installation (gas types & measurements)

- Usable for: NG H/E 20mbar, E+ 20/25mbar
- Liquid gas G30,31 28-30/37mbar
- Preset of liquid gas (28-30/37mbar)
- Nozzle set for Natural gas nozzles (20 mbar) included. Nozzles for all other gas types can be ordered via the customer service. For nozzle change, please contact the customer service.
- Dimensions of the product (HxWxD mm): 53 x 582 x 520
- Required niche size for installation (HxWxD mm) : 45 x 560 x (480 - 492)
- Min. worktop thickness: 30 mm
- Power cord 1.5 m South Africa plug: plug and play, no electrician required for installation.
- Connected load: 7.5 KW