

# Series 6, Gas Hob, 60 cm, Tempered glass, Black PPP6A6B20Z



HEZ298105 Simmer plate HEZ298114 Small pot support

# The tempered-glass gas hob with FlameSelect: achieve perfect cooking results thanks to nine precisely defined power levels.

Product name/family:gas hob w int Built-in / Free-standing: Energy input:	Built-in
Total number of positions that can be used at the sar	me time: 4
Type of control setting devices:	sword knobs
Required niche size for installation (HxWxD): 45 x 56	60-562 x 480-492
mm	
Width of the appliance:	590 mm
Dimensions:	58x590x520 mm
Dimensions of the packed product (HxWxD): 141	x 651 x 578 mm
Net weight:	
Gross weight:	15.0 kg
Residual heat indicator:	Nc
Location of control panel:	Front
Basic surface material:	.Tempered glass
Color of surface:	Black
Color of frame:	Black
Length electrical supply cord:	100.0 cm
EAN code:	
Gas connection rating:	7500 W
Fuse protection:	3 А
Voltage:	220-240 V
Frequency:	50-60 Hz





### Series 6, Gas Hob, 60 cm, Tempered glass, Black PPP6A6B20Z

The tempered-glass gas hob with FlameSelect: achieve perfect cooking results thanks to nine precisely defined power levels.

#### Design

- tempered black hard glass base surface, black
- frameless: install the hob either flush or slightly raised on the worktop
- Cast iron w rubber feet single

### Comfort & Convenience

- step valve 9 steps: precisely adjust the flame in nine defined and repeatable levels.
- Sword Knobs: easily access knobs in front with strong grip for effortless turning.
- Ignition via control knobs: just push and turn the knob to ignite the flame.

#### **Burners and power**

- 4 PC
- Left front: Standard burner up to 1.75 KW (depending on gas type)
- Left rear: Standard burner up to 1.75 KW (depending on gas type)
- Right rear: High speed burner up to 3 KW (depending on gas type)
- Right front: Economy burner up to 1 KW (depending on gas type)

#### Safety

- Flame failure safety device: prevents unwanted gas flow when flame goes out.

### Installation (gas types & measurements)

- Usable for: Liquid gas G30,31 28-30/37mbar
- Preset of liquid gas (28-30/37mbar)
- Dimensions of the product (HxWxD mm): 58 x 590 x 520
- Required niche size for installation (HxWxD mm) :  $45 \times 560 \times (480 492)$
- Min. worktop thickness: 30 mm
- Power cord 1 m South Africa plug: plug and play, no electrician required for installation.
- Connected load: 7.5 KW



# Series 6, Gas Hob, 60 cm, Tempered glass, Black PPP6A6B20Z



