SIEMENS

Fully Automatic Coffee Machine, EQ.9 s500, Stainless steel TI905201RW





Included accessories

1 x scoop

1 x test strip

Pure enjoyment is the finest aroma and a constantly clean milk system.

- ✓ Intelligent Heater inside: The sensoFlow System guarantees maximum espresso indulgence every time, thanks to its ideal, constant brewing temperature
- ✓ steam blast: A fully-automatic steam cleaning after every beverage takes complete care of the daily cleaning of the milk system
- \checkmark Cappuccino: Any coffee or milk speciality at the touch of a button even two cups at the same time
- ✓ baristaMode: Additional aroma settings for true connoisseurs
- \checkmark The most silent fully-automatic espresso maker from Siemens

Features

Technical data

Dimensions of the product (mm) : 382 x 316 x 470 Dimensions of the packed product (HxWxD) (mm) : 510 x 357 x 428 Pallet dimensions : 221 x 80 x 120 Standard number of units per pallet : 24 Net weight (kg) : 11.452 Gross weight (kg) : 13.0 Connection Rating (W) : 1500 Voltage (V) : 220-240 Frequency (Hz) : 50/60 Length electrical supply cord (cm) : 100.0 Plug type : Gardy plug w/ earthing Approval certificates : CE, VDE



SIEMENS

Fully Automatic Coffee Machine, EQ.9 s500, Stainless steel TI905201RW

Features

- # Innovative heating system "senso flow system"
- One-touch function for white coffee, Espresso Macchiato, Latte Macchiato, Cappuccino
- * baristaMode: Additional aroma settings for true connoisseurs
- # 2 steps: Even higher aroma extraction due to adjustable brewing
- speed aromaDouble Shot - Extra strong coffee without compromise in aroma
- # Beverage temperature adjustable individually: ,
- * optional Brita water filter: Improves the coffee's taste and prolongs the appliance's life
- # TFT display with interactive menu
- # superSilent: The most silent fully-automatic espresso maker from Siemens thanks to significant noise reduction
- # : Personal beverage settings for up to 6 persons
- #
- F Coffee outlet yesheight-adjustable: Even 15cm high Latte Macchiato glasses fit underneath
- Cappuccino: Prepare two cups simultaneously for all coffee and milk specialities
- # Removable 2.3 litre water tank
- # early warning when bean container or water tank are close to empty

- # High-value ceramic grinding unit "silent ceram drive"
- * yes: The grinding unit automatically adjusts to bean variety
- One-touch coffee milk specialities with especially fine-pored milk froth thanks to an innovative milk frother
- # Reduced heating-up time: fastest first cup
- # Water pump with 19 bar pressure
- # Active cup warmer; on/off switchable
- # Separate container for pre-grounded coffee
- 15.000 cup warranty: Consistently high appliance quality from the first cup to the 15,000th (valid for non-commercial use within 12 months)
- # steam blast: Fully-automatic steam cleaning of the milk system after every beverage
- All milk nozzle parts are easily removable, easy to clean & dishwasher-proof
- # Automatic quick rinse programme when switched on or off
- # Removable drip dish including container for coffee grounds
- # Fully automatic descaling & cleaning programme
- Display of remaining cups before Decalcification, Cleaning, Change of water filter
- Integrated milk container: easy to remove, fits into the fridge door, dishwasher-proof
- # Bean container with aroma preserving lid for up to 235grams
- # Adjustable grind settings (multilevel)
- # Different display languages available
- # child-proof lock: key lock preventing unintended brewing cycle
- # Length power cord: 1 m
- # Wattage: 1500 W
- # Included accessories: 1 x scoop, 1 x test strip
- Adapter for milk carton seperately available: Decide for yourself if you prefer connecting the integrated milk container or using the adapter to connect any other container, e.g. a milk carton.
- Separately available accessories: cleaning tablets (TZ80001), descaling tablets (TZ80002), BRITA Intenza water filter (TZ70003), care set for fully-automatic espresso makers (TZ80004), adapter for milk carton (TZ90008), milk container (TZ90009)