

Serie | 4

DFR067A50
60 cm#####

A



#####

- ##### 740 m3/h#####
- LED#####
- #####: 6#####

Technical data

Typology :	Pull-out
Approval certificates :	CE, Ukraine, VDE
Length electrical supply cord (cm) :	175
Required niche size for installation (HxWxD) :	385mm x 524mm x 290mm
Net weight (kg) :	10.261
:	Electronic
##### (m3/h) :	400
Boost position output recirculating (m3/h) :	490
##### (m3/h) :	300
Boost position air extraction (m³/h) :	740
Number of lights :	2
#### (dB) :	55
Diameter of air outlet (mm) :	120 / 150
Grease filter material :	Washable aluminium
Odour filter :	No
Delay Shut off modes :	10M
Optional accessories :	DSZ4561, DSZ4565, DSZ4652, DSZ4655, DSZ4656, DSZ4660, DSZ4680, DSZ4681, DSZ4683, DWZ0IT0P0
Type of lamps used :	LED
Total power of the lamps (W) :	6
Grease filter type :	Kassette
Connection Rating (W) :	146
:	10
## (V) :	220-240
Frequency (Hz) :	50; 60
Plug type :	Gardy plug w/ earthing
Material body :	zinc plated
Approval certificates :	CE, Ukraine, VDE
Plug type :	Gardy plug w/ earthing
Dimensions of the product, with chimney (if exists) (in) :	/ x x
Dimensions of the packed product (in) :	15.74 x 25.19 x 18.89
Net weight (lbs) :	23
Gross weight (lbs) :	26
Motor location :	Integrated motor in hood body
No-return airflow flap :	No
Length electrical supply cord (cm) :	175
Dimensions of the product, with chimney (if exists) (mm) :	426 x 598 x 290
Dimensions of the packed product (HxWxD) (mm) :	400 x 640 x 480
Net weight (kg) :	10.261
Gross weight (kg) :	12.0



Serie | 4 Hoods

DFR067A50

60 cm#####

#####

##:

- #####
- 60 cm #
- ###60cm ###
- ####: ####

##:

- #####
- ###: 740m³/h (EN 61591)
- #####
- 3 #####
- #####
- LED #

###:

- #: 146 W
- #####
- ## (#x #x #): 385 x 598 x 290 ##

###:

- 2 #####
- ##150##### (##(120#####))